

STC301

TAG, SENTECH OMNI 8.2 MHZ, BEIGE, WITH 3

Close-Out



.22

Beige color Omni tag is has a high security 3 ball clutch lock for superior tack holding power. The Omni tag gives maximum detection in any 8.2 MHz RF system.

Measures 2.75" X 2.275" (70 X 58 mm),
 Weight each .624 oz. (17.8 g)

SL482CP-12334

LABEL, 1.5" CUSTOM PRINTED, 8.2 MHZ. 1000

Close-Out



.005

8.2 MHz Custom Printed for Navarro Drugs.
 Compatible with any 8.2 MHz RF system.

STC340-01

LABEL BC 8.2 DEAC 1.5"

Close-Out




.01

Deactivatable 8.2 MHz barcoded label compatible with all SenTech 8.2 MHz RF systems and deactivators as well as any competitive 8.2 MHz RF systems using labels. Measures 1.5" (40 mm) square and is rolled in quantities of 1000 per roll.

STC341-01

LABEL PLAIN 8.2 DEAC 1.5"

Close-Out



.01

Deactivatable 8.2 MHz Plain white label compatible with all SenTech 8.2 MHz RF systems and deactivators as well as any competitive 8.2 MHz RF systems using labels. May be printed in standard label printers. Measures 1.5" (40 mm) square and is rolled in quantities of 1000 per roll.

CP316

LABEL, VIDEO FLAP, BLACK, 8.2 MHZ

Close-Out



.03

Non-Deactivatable 8.2 MHz video flap label is placed on the edge of the the VHS video tape or under the flap. It is compatible with all SenTech 8.2 MHz RF systems as well as any competitive 8.2 MHz RF systems using labels. Measures 5.5" X 11/16" (14 cm X 1.75 cm) and is rolled in quantities of 500 per roll.

CP316-ND

LABEL, 1.5", WHT, 8.2 MHZ, NON DEAC

Close-Out



.01

Non-Deactivatable 8.2 MHz Plain white label compatible with all SenTech 8.2 MHz RF systems and deactivators as well as any competitive 8.2 MHz RF systems using labels. May be printed in standard label printers. Measures 1.6" (40.64 mm) square.

CP318-ND

LABEL, 2.0", WHT, 8.2 MHZ, NON DEAC

Close-Out



.057

CP314

LABEL, VIDEO FLAP, BLACK, 9.5 MHZ

Close-Out



.03

Non-Deactivatable 9.5 MHz video flap label is placed on the edge of the the VHS video tape or under the flap. It is compatible with all SenTech 9.5 MHz RF systems as well as any competitive 9.5 MHz RF systems using labels. Measures 5.5" X 11/16" (14 cm X 1.75 cm) and is rolled in quantities of 500 per roll.

SL495BK

LABEL, 1.5" BE KIND, 9.5 MHZ. 1KROLL

Close-Out



.005

Non-Deactivatable 9.5 MHz label printed for use in video stores with "Be Kind Please Rewind" is compatible with all SenTech 9.5 MHz RF systems as well as any competitive 9.5 MHz RF systems using labels. Measures 1.5" (40 mm) square and is rolled in quantities of 1000 per roll.

STC2012-82

TAG, PULL-LOK, 8.2 MHZ. BLACK, (300 CS) 12.5"

Close-Out



.66

The Pull-Lok Tag is made of black ABS plastic and works with any 8.2 MHz system. It has a machined brass high security lock and PVC coated steel cable. It is used to secure large diameter items up to 4.5" Dia. that the lanyard may be pulled tight around and is removed by standard magnetic detachers.

STC2012-95

TAG, PULL-LOK, 9.5 MHZ, 12.5" LANYARD (4"

Close-Out



.66

The Pull-Lok Tag is made of charcoal gray ABS plastic and works with any 9.5 MHz system. It has a machined brass high security lock and PVC coated steel cable. It is used to secure large diameter items up to 4.5" Dia. that the lanyard may be pulled tight around and is removed by standard magnetic detachers.

STC1100-1

TAG, ULTRA-MAN

Close-Out



.10

STC1102

TAG, ULTRATAG®, MINI

Close-Out



.10

STC2199

TAG, 1.990 MHZ. COIL - HEAT SEALED, WHITE

Close-Out



.15

Custom white vinyl heat sealed pouch with embedded RF tag circuit. High detection comparable to Omni tag. May be attached using a Prolock clutch and tack, or may be concealed inside pockets or wallets and purses.

* Any other RF or Magnetic frequencies available

SC3002

TAG, MICROGATOR, BEIGE

Close-Out



.10

Sensormatic® MicroGator® is used with Sensormatic 900 MHz Microwave systems. They are removed with Sensormatic standard Hand Detachers or Power Detachers.

SenTech offers new and refurbished Sensormatic detachers, as well as our new STC540 Hand

SC3011

TAG, 1/2 ALLIGATOR

Close-Out



.03

CP105

TACK, SWIVEL HEAD W/GROVES, 5/8"

Close-Out



.02

Hardened 5/8" flat head steel pin, may be used with any RF hard tag. Has grooved shaft for increased holding power.

STC216

TACK, GREY PLASTIC FOR "NOGO" TAG, DIA.

Close-Out



.05

Large diameter round dome shaped plastic head tack with hardened 9/16" steel pin, may be used with most RF hard tags that are 2.5" (63.5 mm) or larger in diameter. Provides an increased level of security from tampering.

CP106

TACK, SWIVEL HEAD, SMOOTH, 5/8"

Close-Out



.02

Hardened steel pin, may be used with any RF hard tag, head swivels to reduce possibility of breakage.

ST603

INKTAG III, W/ 5/8" PIN, 2 VIAL

Close-Out



.20

DIR2

DETACHER, BLU SAFER

Close-Out



.20

Magnetic detacher for releasing SenTech Blu System Safers

MK35

DETACHER, POWER, MK35

Close-Out



95.00

120 VAC powered, removes SenTech's UltraTag® and all standard Sensormatic® Alligator®, MicroGator®, UltraGator® and MicroClamp tags.

PSC-1

SCANNER, BARCODE, SPECTRA PHYS.


Close-Out

300.00

ML06127-B

LABEL, MAGNETIC, BLACK, NON-DEAC, 5" X

Close-Out



.025

Non-Deactivatable magnetic label used with any Sensormatic®, Knogo®, or compatible magnetic system.

Label dimensions are 5" X 1/4" (127mm X 6mm)




2843 Centerport Circle, Pompano Beach, Florida 33064 USA
 Toll Free: 800-331-4675 • Direct: 954-426-2965 • Fax: 954-426-8389 • www.sentecheas.com

ML0690-B

LABEL, MAGNETIC, BLACK, NON-DEAC, 3.5" X

Close-Out



.024

Non-Deactivatable magnetic label used with any Sensormatic®, Knogo®, or compatible magnetic system.

Label dimensions are 3.5" X 1/4" (90mm X 6mm)

DVD100

DVD, CASE, CLEAR, 9.5 MHZ, W/ DVD101 THICK

Close-Out



.50

The SenTech DVD security case is designed to provide excellent security for DVD and CD rental applications. It secures the DVD or CD by locking it through the center hole. A magnetic super detacher is required to remove the locking tack. The DVD case is then passed around the security system allowing the renter to exit the store without

DVD100-AM

DVD, CASE, CLEAR, 58 KHZ (AM) (FERRITE),

Close-Out



.50

The SenTech DVD security case is designed to provide excellent security for DVD and CD rental applications. It secures the DVD or CD by locking it through the center hole. A magnetic super detacher is required to remove the locking tack. The DVD case is then passed around the security system allowing the renter to exit the store without

DVD101

TACK, THICK PLASTIC HEAD, SS, ONE

Close-Out



.03

Plastic head tack designed for use with the SenTech DVD100 security case. The plastic head is shaped to allow easy removal. It is made of light gray ABS plastic with a hardened stainless steel pin. The pin also has a one groove shaft providing a positive lock that is highly resistant to unauthorized removal.

ST300

TAG, HARD - SECURITY TAG

Close-Out



.05

Original Security Tag used with dual frequency systems manufactured by Security Tag Systems or Xponder. Uses standard magnetic detachers.

CP311

VERIFIER, PORTABLE HAND, CHKPT # 631117

Close-Out



50.00

Detects 8.2 MHz RF labels and tags concealed in bags or on person.

2200-0001

SPEAKER, 4" X 6", 4 OHM, #KS46GM4

Close-Out



1.00

2200-0004

SPEAKER, 2" DIA, 45 OHM, .2W #BL50A-45

Close-Out



.25

CD1020-VA

Close-Out



120.00

The CD1020-VA is a compact 420 TVL, 1/3" format Digital CCD Mini dome camera. Features Sony Super HAD Technology. Includes varifocal auto iris lens making it ideal for a large variety of applications. Operates on 12 VDC, works well in low light conditions at 0.2 LUX.

ED300

Close-Out



100.00

The ED300's advanced digital signal processing provides users with the sharpest image possible. The dome also features a built-in varifocal lens for discreet surveillance or close-up viewing.

See PDF spec sheet for more detailed information.

VSE-P6361DSB

CAMERA, SANYO 6" DOME 480 TVL 2.8-12MM

Close-Out



125.00

- * Camera 480 TVL High Resolution Color
- * 3.5-8mm, 2.8-12mm Varifocal Lenses w/auto iris
- * 3-pivot Camera Adjustment System
- * 360° Pan and 180° Tilt Positioning
- * Black Trim Ring

VSE-P6362DSB

CAMERA, SANYO 6" DOME 480 TVL 5-50MM VF

Close-Out



125.00

- * Camera 480 TVL High Resolution Color
- * 3.5-8mm, 5-50mm Varifocal Lenses w/auto iris
- * 3-pivot Camera Adjustment System
- * 360° Pan and 180° Tilt Positioning
- * Black Trim Ring

VCC-4594

Close-Out



100.00

Super high-resolution of 520 horizontal TV lines. Intelligent backlight compensation. High performance with minimum required illumination of 0.03 lux (F 1.2 lens in B/W mode). Digital signal processing (DSP) for sharper, clearer color images

VCC-6574A

CAMERA, SANYO, COLOR, DIGITAL 24VAC, 520

Close-Out



100.00

Super High Resolution -- 520 TV Lines of Resolution • High Sensitivity of 0.9 lux @f1.2
 Smart Multi-zone Weighted BLC • New DSP Circuitry, DC & Video Auto-iris lens compatibility

VCC-6594

Close-Out



100.00

Sanyo VCC-6594 1/3" Super High Resolution, High Sensitivity DSP Color Camera High-Resolution Technology 520 Lines of Horizontal Resolution 1/3" CCD Image Sensor Approx. 410,000 Picture Elements Digital Signal Processing (DSP) Circuit 2 Mode Back Light Compensation High Sensitivity, Minimum Required Illumination .03 Lux @ F1.2

VCC-WD8574

CAMERA, SANYO, COLOR 480 TVL, .05 LUX 12

Close-Out



100.00

450TV Lines of Resolution • Day / Night wide dynamic range.
 Dual power operation uses either 24VAC or 12VDC

13VG2812AS-SQ

LENS, TAMRON, AUTO IRIS VARIFOCAL, 2.8

Close-Out



50.00

Focal Length 2.8-12mm
 Iris Range F/1.4 to 360
 Iris Operation Auto Iris (DC) w/ 4 pin square conn.
 Focus Operation Manual
 Mount CS

13VG308AS-SQ

LENS, TAMRON, AUTO IRIS VARIFOCAL, 3-8MM

Close-Out



36.00

Focal Length 3-8mm
 Iris Range F/1.0 to 360
 Iris Operation Auto Iris (DC) w/ 4 pin square conn.
 Focus Operation Manual
 Mount CS

DSR-3009H160

DVR WITH 9 CHANNEL MULTIPLEXER, 160GB,

Close-Out



1500.00

Digital Video Recorder with Integrated 9-Channel Multiplexer 160GB Internal Capacity, Plug 'N' Play External Expandability to 960GB, 60fps Digital Triplex Capability – Simultaneously Record, View Live, Internet Control, Audio Recording, Alarm/Motion Only Recording, Easy Search Capability, Motion Search on Playback, Time/Date

PE-VS5104

Close-Out



109.00

Low cost, desktop, sequential switcher. See product data sheet for complete information.

PIH-302

Close-Out



75.00

Lightweight internal Pan & Tilt head for fully functional cameras. The AC motors are available in a wide range of voltages and provide 6 degree/second panning speed and 4 degree/second tilt.

The pan range is 350 degree can be limited by

PIH-308

Close-Out



210.00

Provides full control of up to 5 PTZ's, via hardwire connections as opposed to telemetry control. The 5 main rocker switches control movement left/right and up/down along with zoom, focus and manual iris. There is also an adjustable control for altering the speed of the lens functions. A range of voltage options are available depending on the requirements

AX-ALTV244

POWER SUPPLY, 4 OUTPUTS, 24VAC 4 AMP

Close-Out



50.00

UL Listed power supply capable of powering up to four cameras. Has four Individually fused outputs with screw terminal connections.

2100-0068

CONN, BNC, MALE, TEFLON RG59, CRIMP, 3

Close-Out



.48

BNC male connector for RG59 cable, nickel plated with teflon insulator, 3 piece crimp style for CCTV camera installation.